## CS SERIES RIBBED COMMERCIAL



# RIBBED CS20 | CS24 | CS26

#### DURABLE ROLL-FORMED STEEL

Each starts with a strong, 2-inch ribbed base for added strength, and uses pebble-grain textured steel in 20-, 24- or 26-gauge thickness for durability. We spot-weld the CS20 and CS24 doors by hand for greater structural integrity than the many bolt-together doors on the market.

### COLORS









Coffee CS24, CS26



The ColorSelect<sup>™</sup> process uses a Sherwin Williams Polane® Solar Reflective Polyurethane Enamel that utilizes the latest technologies to provide a durable, heat-repelling coating.

Due to the printing process, colors may vary.

### INSULATION

	CS20	CS24	CS26
Foam/Insulate	Plain Steel/ T-Bond	Plain Steel/ T-Bond	Plain Steel/ T-Bond
R-Value	T-Bond: 7.0	T-Bond: 7.0	T-Bond: 7.0
U-Factor (Btu/hr/ft2/F)	0.376	0.376	0.376
Thickness	2 inches	2 inches	2 inches
Maximum Width	40 ft 2 in	26 ft 2 in	16 ft 2 in
Exterior Steel	20 gauge	24 gauge	26 gauge
Warranty* Excludes Springs	10 years	10 years	25 years
"For full warranty details contact your Midland dealer			

#### WINDOWS



GLASS

Choose from Plain, Obscure, Frosted, Gray Tinted, Bronze

Tinted, LoE, and Double Dark

### TRACK MOUNTING



Bracket Mounted Track To attach to wood jambs

#### Angle Mounted Track Continuous leg-out angle used on larger doors to attach to wood jambs



Continuous leg-in angle to attach to steel jambs

# 

TRACK CONFIGURATIONS


Standard Lift For normal installations





Inclined Track To follow pitch of roof





YOUR LOCAL GARAGE DOOR DEALER



PLACE YOUR ORDER TODAY

MIDLANDGARAGEDOOR.COM | 800.437.4056

